

Hydraulic Power Packs



CABLE PULLING

Portable Hydraulic Power Packs

These portable power sources are matched perfectly to the power requirements of the Condux Fiber Optic Cable Puller and the Fiber Optic Cable Blower. Power source is a 5.5 HP (4.1 kW) Honda (gas), 9 HP (6.7 kW) Honda (gas), or a 16 HP (11.9 kW) Briggs & Stratton V-Twin Vanguard (gas) engine. Features electric start, large capacity hydraulic cooler, quick disconnects, low oil shut-off and 16" (406 mm) diameter pneumatic tires.

Part Number	Description
08675750	5.5 HP Hydraulic Power Pack, gas (4.5 GPM @ 1500 psi) Dry - International Unit*
08675760	5.5 HP Hydraulic Power Pack, gas (4.5 GPM @ 1500 psi) Wet - Domestic Unit
08675700	9 HP Hydraulic Power Pack, gas (5.9 GPM @ 1800 psi)
08675200	16 HP Hydraulic Power Pack, gas (8.2 GPM @ 2000 psi)
08675210	16 HP Hydraulic Power Pack Cover

*International shipments only.



Specifications

Power Pack Size	5.5 HP Hydraulic Power Pack	9 HP Hydraulic Power Pack	16 HP Hydraulic Power Pack
Use Product	LW Fiber Optic Cable Blower	HD Fiber Optic Cable Blower	Fiber Optic Cable Puller
Part Number	08675760 - Wet (Domestic) 08675750 - Dry (International)	08675700	08675200
Hyd. System	Open Center	Open Center	Open Center
Frame Type	Two wheel mobile unit	Two wheel mobile unit	Two wheel mobile unit
Length	23.5 in (597 mm)	26.5 in (673 mm)	35.0 in (889 mm)
Width	17.0 in (432 mm)	20.0 in (508 mm)	29.0 in (736 mm)
Height	21.0 in (533 mm)	27.5 in (698 mm)	32.0 in (812 mm)
Weight (Dry)	94 lbs (42.6 kg)	143 lbs (64.9 kg)	233 lbs (105.6 kg)
Filtration	10 Micron Return Line Canister Type	10 Micron Return Line Canister Type	10 Micron Return Line Canister Type
Oil Cooler	Air to Oil	Air to Oil	Air to Oil
Engine	Gas Honda, 5.5 HP (4.1 kW) @ 3,900 RPM	Gas Honda, 9 HP (6.7 kW) @ 3,600 RPM	Gas Briggs & Stratton V-Twin Vanguard, 16 HP (11.9 kW) @ 3,600 RPM
Fuel	.97 gallons/3.67 liters	1.6 gallons/6.1 liters	5.0 gallons/18.9 liters
Hydraulic Oil (Useable)	1.75 gallons/6.62 liters	5.0 gallons/18.9 liters	5.0 gallons/18.9 liters
Hydraulic Rated Flow	GPM @ PSI	GPM @ PSI	GPM @ PSI
	LPM @ BAR	LPM @ BAR	LPM @ BAR
Hydraulic Relief Valve Pressure	1,800.0 PSI (123.2 BAR)	2,150.0 PSI (148.3 BAR)	2,150.0 PSI (148.3 BAR)



Hydraulic Power Pack Accessories

Part Number	Description
08675858	Hydraulic Hose Kit, 20' (6 m) Hose with Couplings
08780384	Hydraulic Hose with flow control manifold
02260000	Hydraulic Coupling, Female Flat Face Faster 2FFN38-12NPT-F / Bruning FF371-8FP
02260100	Hydraulic Coupling, Male Flat Face Faster 2FFN38-12NPT-M / Bruning FF372-8FP
02260200	Dust Cap, Male Coupling
02260201	Dust Cap, Female Coupling
02286416	Power cord assembly extension, 2-pin straight, 20' (6 m)
08675240	Power cord adapter for Fiber Optic Puller



Dust Caps

Couplings