

Telephone Duct – Type B, C & D



Telephone Duct Type B

Carlton® Telephone Duct Type B is designed for use in concrete encased installations. Type B duct meets the requirements of NEMA TC-10 and conforms to Bellcore CA08546.



Telephone Duct Type B

Nom. Size	Part Number	Std. Crate Qty.	Approx. Wt. per 100 ft.	O.D.	*Min. Wall
4"	68315-020 (Grey)	1260	100	4.350	.090
4"	68315W-020 (White)	1260	100	4.350	.095

Telephone Duct Type B Heavy Wall

Nom. Size	Part Number	Std. Crate Qty.	Approx. Wt. per 100 ft.	O.D.	*Min. Wall
4"	68415-020 (Grey)	1260	100	4.350	.100
4"	68415W-020 (White)	1260	100	4.350	.100

* Estimated min. wall to meet performance criteria (500,000 modulus compound)
NOTE: One Belled End per 20' length (for concrete encasement only)

Telephone Duct Type C

RUS Listed

Carlton® Telephone Duct Type C is designed for direct burial or concrete encased applications. Type C duct complies with NEMA Standard TC-10 and Bellcore CA08546.



Telephone Duct Type C

One belled end per 20' length

Nom. Size	Part Number	Std. Crate Qty.	Approx. Wt. per 100 ft.	O.D.	*Min. Wall
4"	68515-020 (Grey)	1260	151	4.350	.150
4"	68515W-020 (White)	1260	151	4.350	.150

* Estimated min. wall to meet performance criteria

Telephone Duct Type D

RUS Listed

White Only (Carlton® Telephone Duct Type D is designed to be used in exposed applications.)



Telephone Duct Type D

Nom. Size	Part Number	Std. Crate Qty.	Approx. Wt. per 100 ft.	O.D.	*Min. Wall
4"	68615-020 (White)	1260	150	4.350	.160

* Estimated min. wall to meet performance criteria