



PE & PVC Pulling Eyes



PE & PVC Pulling Eyes

Condux PE & PVC Pulling Eyes provide optimum gripping power and a watertight design. The watertight pulling eyes feature a multiple o-ring configuration, an extremely rigid center rod to prevent bending and a steel tapered lead cone with the same OD as the conduit. These design features protect the outer leading edge of the conduit and form a watertight seal. Condux PE & PVC Pulling Eyes also feature split gripping segments with aggressive gripping threads coupled with a steel expander plug that better grips the full range of conduit I.D.s.

Installation of the PE & PVC Pulling Eyes simply requires the leading eye to be tightened. The pulling eyes come standard with attachment eyes at both ends for connecting rope or steel lines. Pull-out strengths generally exceed the tensile capacity of the conduit.

See Ordering Information page 65.

NOTE: PE & PVC Pulling Eyes come with a 90 day limited warranty.



PE & PVC Pulling Eyes



Part No.	Size in (mm)	Length in (mm)	Conduit ID in (mm)		Lead Cone O.D. in (mm)	Duct Type	Nom. Duct I.D. in (mm)
			Min.	Max.			
08220600	1 1/4 (32)	6.23 (158)	1.25 (32)	1.50 (38)	2.00 (51)	1.25 SDR 11.0	1.33 (34)
						1.25 Sch 40	1.38 (35)
						1.25 SDR 13.5	1.39 (35)
						1.25 SDR 15.5	1.43 (36)
						1.25 SDR 17.0	1.44 (37)
08220601	1 1/2 (38)	6.23 (158)	1.50 (38)	1.75 (44)	2.25 (57)	1.25 SDR 21.0	1.50 (38)
						1.5 SDR 11.0	1.53 (39)
						1.5 SDR 13.5	1.60 (41)
						1.5 SDR 40	1.61 (41)
						1.5 SDR 15.5	1.63 (41)
08220602	2 (51)	8.18 (208)	1.88 (48)	2.15 (55)	2.75 (70)	1.5 SDR 17.0	1.66 (42)
						1.5 SDR 21.0	1.72 (44)
						2.0 SDR 11.0	1.92 (49)
						2.0 SDR 13.5	2.00 (51)
						2.0 SDR 15.5	2.05 (52)
08220609	2 1/2 (64)	8.80 (224)	2.31 (59)	2.56 (65)	3.31 (84)	2.0 Sch 40	2.07 (53)
						2.0 SDR 17.0	2.08 (53)
						2.0 SDR 21.0	2.15 (55)
						2.5 SDR 11.0	2.32 (59)
						2.5 SDR 13.5	2.42 (61)
08220603	3 (76)	11.89 (302)	2.69 (68)	3.13 (79)	4.00 (102)	2.5 Sch 40	2.47 (63)
						2.5 SDR 15.5	2.49 (63)
						2.5 SDR 17.0	2.51 (64)
						3.0 SDR 11.0	2.83 (72)
						3.0 SDR 13.5	2.95 (75)
08220604	4 (102)	14.11 (358)	3.50 (89)	4.06 (103)	5.00 (127)	3.0 SDR 15.5	3.02 (77)
						3.0 SDR 17.0	3.06 (78)
						3.0 Sch 40	3.07 (78)
						4.0 SDR 11.0	3.63 (92)
						4.0 SDR 13.5	3.79 (96)
08220605	5 (127)	18.45 (469)	4.25 (108)	5.06 (129)	6.00 (152)	4.0 Sch 80	3.83 (97)
						4.0 SDR 15.5	3.89 (99)
						4.0 SDR 17.0	3.94 (100)
						4.0 Sch 40	4.03 (102)
						4.0 SDR 21.0	4.05 (103)
08220606	6 (152)	19.60 (498)	5.06 (129)	6.00 (152)	7.13 (181)	5.0 SDR 11.0	4.49 (114)
						5.0 SDR 13.5	4.69 (119)
						5.0 SDR 15.5	4.80 (122)
						5.0 SDR 17.0	4.87 (124)
						5.0 SDR 21.0	5.00 (127)
08220608	8 (203)	21.53 (547)	6.63 (168)	7.69 (195)	9.25 (235)	5.0 Sch 40	5.05 (128)
						6.0 SDR 11.0	5.35 (136)
						6.0 SDR 13.5	5.58 (142)
						6.0 SDR 15.5	5.72 (145)
						6.0 SDR 17.0	5.80 (147)
*08220510	10 (254)	25.48 (647)	8.25 (210)	9.75 (248)	11.19 (284)	6.0 SDR 21.0	5.96 (151)
						8.0 SDR 11.0	6.96 (177)
						8.0 SDR 13.5	7.27 (185)
						8.0 SDR 15.5	7.45 (189)
						8.0 SDR 17.0	7.55 (192)
*08220021	12 (305)	28.75 (730)	10.13 (257)	11.38 (289)	13.50 (343)	10.0 SDR 11.0	8.68 (220)
						10.0 SDR 13.5	9.06 (230)
						10.0 SDR 15.5	9.28 (236)
						10.0 SDR 17.0	9.41 (239)
						10.0 SDR 21.0	9.67 (246)
*08220031	14 (356)	28.75 (730)	11.25 (286)	12.50 (318)	14.75 (375)	12.0 SDR 11.0	10.43 (265)
						12.0 SDR 13.5	10.86 (276)
						12.0 SDR 15.5	11.10 (282)
						12.0 SDR 21.0	11.25 (286)
						14.0 SDR 11.0	11.45 (291)
						14.0 SDR 13.5	11.93 (303)
						14.0 SDR 15.5	12.19 (310)
						14.0 SDR 21.0	12.35 (314)

* These eyes are sleeved but ARE NOT watertight.