

GasAlertMax

H₂S, CO, O₂ and %LEL

"INNOVATORS IN GAS DETECTION"



Multi-Gas Detectors



Protect Yourself

- ▲ Large LCD shows real-time gas concentrations of H₂S, CO, O₂ and %LEL
- ▲ Internal plug-in pump for remote sampling
- ▲ LOW, HIGH, TWA and STEL alarms with adjustable setpoints
- ▲ Equipped with plug-in, replaceable sensors
- ▲ Simple, automatic calibration procedure
- ▲ Intrinsically safe to U.S., European and Canadian standards
- ▲ Provides 95 dB tone and bright LED indication on alarm
- ▲ Compact (1.6 x 3.0 x 5.9 in / 40 x 75 x 150 mm) and lightweight (15.4 oz. / 396 g)
- ▲ Runs an entire shift on one Black & Decker VersaPak™ rechargeable battery (available worldwide)
- ▲ Peak values displayed on command
- ▲ Full-function self-test of: sensor/battery/circuitry integrity; and audible/visual alarms
- ▲ One VersaPak rechargeable battery, 2-port charger, 10 ft. / 3m. sampling hose, calibration hose, carrying holster, and instructions in local languages included
- ▲ Vibrating alarm and remote audible/visual alarm (110 dB) accessories available



BAM ATEX



Plus Others

Ordering Information

Gas Detectors (Standard)

GAMAX3-4	4-gas: H ₂ S, CO, O ₂ , LEL
GAMAX3-3H	3-gas: H ₂ S, O ₂ , LEL
GAMAX3-2	2-gas: O ₂ , LEL

- Add suffix: -DL1 for black box datalogger
 -DL2 for user downloadable datalogger
 *Note: Comes with free software and 32 MB MMC Card
- Add suffix for delivery with 200 VAC Charger:
 -EU -UK -AU -NZ -OR
- Add suffix -A (to omit VAC charger and batteries)

Accessories

GA-VIB3	Remote vibrator alarm
CG-Q58-4	Quad calibration gas cylinder (58L)
CG-BUMP2	Bump test gas aerosol (11L)
GA-BMAX	Concussion-proof boot
GA-BMAX-3	Concussion-proof boot with neck strap
GA-VP110	VersaPak™ rechargeable NiMH battery
GA-VP100	VersaPak™ rechargeable NiCAD battery
D4-VP140	2 port, 12 volt, Black & Decker vehicle charger

Georgia Underground
 Is Your Utility Products
SUPERSTORE

800.245.8339

www.georgiaunderground.com



GasAlertMax

H₂S, CO, O₂, LEL

Four Gas Detector with Internal Sampling Pump

GasAlertMax provides extraordinary cost of ownership advantages. Training and maintenance costs are minimized through automated calibration, internal plug-in sampling pump, long-life VersaPak battery power (available in local stores) and simple, one-button control. GasAlertMax is powered by two advanced microcontrollers and features plug-in electrochemical and catalytic sensors. High-output audible/visual alarms provide instant notification.

The large alphanumeric LCD shows real-time gas concentrations and the instrument's status at all times. A full-function self-test verifies sensor, circuitry and battery integrity and activates the audible/visual alarms each time the detector is activated. GasAlertMax clearly advises the hazard present—Low, High, TWA and STEL multi-gas alarm. Recorded TWA, STEL and Peak exposures can be displayed on demand.

GasAlertMax satisfies the OSHA safety regulation CFR1910.146 (Permit Required - Confined Space Entry).

SPECIFICATIONS

DETECTOR: 2, 3 or 4-gas detector

Gas:	H ₂ S	CO	O ₂ (% by vol.)	Combustibles
Measuring Range:	0 - 100 ppm	0 - 500 ppm	0 - 30.0 %	0 - 100 % LEL
Low alarm level ¹ :	10 ppm	35 ppm	19.5 %	10 %
TWA alarm level ¹ :	10 ppm	35 ppm	N/A	N/A
High alarm level ¹ :	15 ppm	200 ppm	23.5 %	20 %

Auto zero: Yes
 Calibration: Automatic
 Backlight: Low light (auto); alarm condition (auto); reactivation on demand
 Full function self-test: Sensor integrity, circuitry and battery; audible/visual alarms
 Sensor: Plug-in, electrochemical cell (toxic and oxygen); catalytic (LEL)
 User field options: Confidence beep, pass code protection, latching alarms and sensor on/off and user selectable span values
ALARM INDICATORS:
 Visual alarm: Clearly advise alarm levels both visually and audibly
 Audible alarm: Flashing, wide-angled alarm lens with dual red LEDs, plus alarm LCD readout
 Confidence beep: High-output, variable, pulsing siren 95 dB at 1 ft. / 0.3 m
 Other: Every 5 seconds (field-selectable)
 Remote alarm (option): Low battery; off warning; sensor fail; multiple gas hazard
 Accepts vibrating alarm or remote audible/visual alarm (110 dB)

LCD: Continuous, alphanumeric gas readout and status display advises:
 Gas ppm or %: Simultaneously and continuously displays all 4 gas concentration(s) present
 TWA ppm or %: Records and displays on demand and during alarm
 Peak ppm or %: Records and displays peak exposure to gas and displays on demand
 Setpoints: Displayed on activation (auto) and on demand in ppm or %

TESTS:
 Full-function self-test: Full-function self-test on activation (auto)
 Battery: Continuous (auto)

GENERAL SPECIFICATIONS: Impact-resistant ABS enclosure
 Operating Temperature: -4 to 122 °F / -20 to 50 °C (Australia -20 °C to 40 °C)
 North America (cCSAus) 132 °C(T4) at 50 °C
 Europe (ATEX) 184 °C at 50 °C
 Australia (SA) 213 °C

Humidity: 5% to 95% RH (non-condensing)
 EMI/RFI: Complies with EMC Directive 89/336/EEC
 Battery type: One 3.6 volt Black & Decker VersaPak rechargeable cell
 Battery run-time: NiMH: up to 12 hours operation; NiCd: up to 8 hours operation
 Size: 1.6 x 3.0 x 5.9 inches / 40 x 75 x 150 mm
 Weight: 15.4 oz. / 396 g

WARRANTY: Full 2 year warranty including all sensors

DATALOGGER OPTIONS: User-downloadable datalogger
 Data recorder: All events and occurrences
 Sampling rate: Factory set at 5-second intervals and user-settable from 1 to 127-second intervals
 Storage: 4.4 months of continuous data via 32 MB Flash MMC card (64 MB cards are also available); when full, the wraparound feature replaces oldest data with most recent data

¹Factory defaults are shown (alarm levels are field-settable).

²Temperature codes may vary as function of battery installed. Please see owner's manual for compatible listing

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.

RATINGS AND CERTIFICATIONS: (Intrinsic safety)

CSA: Class I, Div. 1, Gr. A, B, C, D

ATEX: CE (E) II 2 G
 EEx ia d IIC

BAM: certified by BAM to the Oxygen and Combustible Performance standards CO and H₂S

ANSI/ISA: ISA-S12.13

CSA: C22.2 No 152

CE: European Conformity

Australia: Ex ia s IIB

"INNOVATORS IN GAS DETECTION"



- 1 LARGE, HIGH-CONTRAST LCD
- 2 WIDE-ANGLED VISUAL ALARM BAR
- 3 HIGH-OUTPUT 95 dB SIREN
- 4 ADVANCED MICROCONTROLLER-BASED OPERATION
- 5 AUTO BACKLIGHT
- 6 SIMPLE CONTROLS
- 7 VersaPak RECHARGEABLE BATTERY
- 8 BUILT-IN SAMPLING PUMP



Training CD-ROM

Auto Zero

Auto Span

Fully automatic calibration



Records / displays TWA and Peak (MAX) gas exposures

Locally distributed by:

